



Lead Free FTG x C Reducing Coupling (317 Series)

Dimensions (in)

Part Number	Nominal Size	OD Size
317-5850	5/8" x 1/2"	3/4" x 5/8"
317-7525	3/4" x 1/4"	7/8" x 3/8"
317-7550	3/4" x 1/2"	7/8" x 5/8"
317-1050	1" x 1/2"	1-1/8" x 5/8"
317-1075	1" x 3/4"	1-1/8" x 7/8"
317-1210	1-1/4" x 1"	1-3/8" x 1-1/8"
317-1275	1-1/4" x 3/4"	1-3/8" x 7/8"
317-1510	1-1/4" x 1"	1-5/8" x 1-1/8"
317-1512	1-1/2" x 1-1/4"	1-5/8" x 1-3/8"
317-1575	1-1/2" x 3/4"	1-5/8" x 7/8"
317-2010	2" x 1"	2-1/8" x 1-1/8"
317-2012	2" x 1-1/4"	2-1/8" x 1-3/8"
317-2015	2" x 1-1/2"	2-1/8" x 1-5/8"
317-2050	2" x 1/2"	2-1/8" x 5/8"
317-2075	2" x 3/4"	2-1/8" x 7/8"
317-2510	2-1/2" x 1"	2-5/8" x 1-1/8"
317-2515	2-1/2" x 1-1/2"	2-5/8" x 1-5/8"
317-2520	2-1/2" x 2"	2-5/8" x 2-1/8"
317-3020	3" x 2"	3-1/8" x 2-1/8"
317-3025	3" x 2-1/2"	3-1/8" x 2-5/8"



Specifications

- Product is designed to join ASTM B280, ASTM B743 and ASTM B88
- Copper fittings made from UNS C12200 grade of copper and compliant with ASTM B75
- Fittings shall conform to ASME B16.22 and MSS